



SV150T	VOLTAGE	ENDGLOW COLOR WHEEL	CONTROL SYSTEM
<b>150 watt</b> metal halide tower illuminator	<b>120</b> - 120 VAC, 60 Hz	<b>1</b> - none	<b>N</b> - none
<b>LAMP</b>	<b>220</b> - 220 VAC, 50 Hz	<b>6</b> - 6 standard	<b>C</b> - Sync. / instant color change*
<b>40-GA</b> - 4,000K			* no need for SV300C or SV600C

**SPECIFICATIONS:**

UL Listed: for Wet Locations

**Electrical Rating:**

- 120 VAC, 60 Hz / 3 Amps (start up)
- 120 VAC, 60 Hz / 1.8 Amps (running)
- 220-240 VAC, 50 Hz / 3.0 Amps (start up)
- 220-240 VAC, 60 Hz / 1.2 Amps (running)

**Lamp:**

- 150 watt metal halide - 4,000K
- 10,000 hours average life

**Fiber Capacity:**

- 550 fibers maximum w/.75mm fibers -
- 288 fibers - Ultra SideGlow™ 1mm
- 756 fibers maximum (upgrade) .75mm
- 435 fibers maximum - Ultra Sideglow™ (upgrade) 1mm

**Power Consumption:**

- 200 watts max.

**Storage Temperature:**

- -40°F to 140°F
- -40°C to 60°C

**Ambient Operating Temperature:**

- -20°F to 110°F
- -29°C to 44°C

**Motors:**

- 1RPM motor

**Dimensions:**

- 9.5" x 9.5" x 20"
- 241mm x 241mm x 508mm

**Weight:**

- 21 lbs.
- 9.5 kg.

**Material/Finish:**

- UV stabilized materials
- Water, corrosion and chemical resistant

**Mounting / Installation:**

- Surface or burial mount up to area below fan location.

**Standard Features:**

- On/off power and color wheel switch
- Dial for color timing (control only) 3 sec - 1 hr continuous adjustment

**Ventilation:**

- Forced ventilation 115 CFM, FAN: 20 Watts, 80,000 hrs. life 6" clearance required to nearest surface. 2' clearance between each illuminator.

**Warranty:**

- 1 Yr. (excluding lamp)

**Upgrades:**

- White only to 6 colors
- 550 - 756 fiber head
- RF controlled light source (surface)

**Standards:**

- UL / cUL

IP Rating: 23



SV150T - Tower illuminator • 150 watt metal halide lamp • 10,000 hour lamp life • 550 (.75mm) strand fiber capacity • 756 (.75mm) strand fiber capacity upgrade (sold separately)



**Screw Driver**

Part No.: 16.0099

Description: screw driver to adjust color wheel speed for 150T6C only

Carton Qty: 1



**Remote Control**

Part No.: SVRFCK\*

Description: remote control for SV150T - order separately

Carton Qty: 1



**Replacement Color Wheel**

Part No.: 6S-HC

Description: color wheel for SV150T

Carton Qty: 1



**SVIS0T6C Data Cable**

Part No.: 17.0609

Description: data cable for controlled tower unit. Sold per foot.



**150T Replacement lamp**

Part No.: 40-GA (4000K)

Description: 150 watt MH/HID replacement lamp for illuminator SV150T.

Carton Qty: 1

	150T
INDOOR	✓
OUTDOOR	✓
FIBER CAPACITY* *.75mm	500 288(1mm)
CE / UL CUL	✓
LAMP TYPE	150W HID
LAMP LIFE	10,000 HRS
POWER (VAC)	120 220
CONTROL SYSTEM OPTION	SYNC REMOTE*
MOUNTING	ON GROUND
COLOR WHEEL OPTION	6-COLOR

\* No need for SV300C or SV600C

	150T
SIDEGLOW®	✓
STAR CEILING	
ARCHITECT LIGHTING FIXTURES	
CHANNEL LETTERS	
LANDSCAPE	✓
POOL & SPA	✓