



DESCRIPTION

This series illuminator has a 70 watt metal halide lamp rated at 9000 lamp hours average life. UL and cUL listed for wet and dry applications. Recommended for endpoint fiber applications: signs, ceilings, floors and wall murals.

SPECIFICATION FEATURES

UL Listed for Dry Locations

Electrical Rating:

- 120 VAC, 60 Hz / 0.9 Amps
- 220 VAC, 50 Hz/ 0.45 Amps

Transformer:

- Electronic

Lamp:

- 70 watt metal halide
- 9000 hours average life
- Color temperature - 3000 K

Power Consumption:

- 100 watts max.

Fiber Capacity:

- 2500, 0.75 mm fibers

Safety Features:

- Internal 185°F/85° C thermal protector

Ambient Operating Temperature:

- -20°F to 110°F
- -29°C to 44°C

Dimensions:

- 8.25" W* x 12.5" L x 6.5" H
- 209mm x 318mm x 165.mm

* add 15" (381mm) for fiber head and fiber to "W" position.

Weight:

- 7 lbs.
- 3.2 kg

Material/Finish:

- Powder coating, no bare metal, inside or outside
- Water, corrosion and chemical resistant

Mounting / Installation:

- Surface or wall mount

Standard Features:

- On/off power and color wheel switch

Ventilation:

- 115 CFM enclosure cooling

Warranty:

- 1 Year (excluding lamp)

ORDERING INFORMATION

| | | | |
|-------------------------------------------------------------------|-------------------------------------------------------------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|---------------------------------------------------------------|
| | | | |
| <p>MODEL StarPro - 70 watt metal halide 3000 K</p> | <p>POWER 120 - 120 VAC, 60Hz 220 - 220-240VAC, 50 Hz</p> | <p>COLOR WHEEL EndGlow® Color Wheels: ESTDC - standard (red, green, blue, yellow) ESTDS - sparkle (red, green, blue, yellow) EWS - sparkle white ESG - standard grey (soft sparkle effect)</p> | <p>CONTROL SYSTEM N - None S - Synchronous</p> |