



ultra sideglow[®] specifications



sv42Ultra



sv84Ultra

DESCRIPTION

The Ultra SideGlow[®] cable has the same features as standard SideGlow[®] cables, with the exception of 25% larger diameter individual fibers. The result is the brightest SideGlow[®] cable available in the industry today!

The Ultra SideGlow[®] cable is made up of .040" / 1.0 mm diameter PMMA acrylic optical fibers protected within a flexible clear pvc jacket. The fibers are twisted around a highly reflective white PVC center core that offers flexible stability with maximum light output.

P-Clips or Track tubing can also be used in mounting the Ultra SideGlow[®] cable.

SPECIFICATION FEATURES

Fixture Construction

The Ultra SideGlow[®] cable is made up of .040"/1.0mm diameter PMMA acrylic optical fibers twisted within a flexible clear jacket. The fibers are twisted around a highly reflective PVC internal core that offers flexible stability with maximum light output.

Cabling

The cable diameter is determined by fiber quantity:

- 42 fibers: 1/2"
- 84 fibers: 5/8"

Warranty

One year warranty on all parts and workmanship

ORDERING INFORMATION

ULTRA SIDEGLOW[®] CABLES

(Order separately)

sv42Ultra 42 fibers

sv84Ultra 84 fibers