



## DESCRIPTION

Wet and dry UL listed illuminator with a 250 watt HID lamp rated at 6000 hours average life. Recommended for SideGlow™ interior and exterior applications.

## SPECIFICATION FEATURES

UL Listed: Wet and dry Locations

Electrical Rating:

- 120 VAC, 60 Hz / 3.5 Amps
- 220-240 VAC, 50 Hz / 3.0 Amps
- 277 VAC, 50 Hz / 3.0 Amps
- 5.0 Amps Inrush Current

Transformer:

- MAGNETIC

Lamp:

- 250 watt metal halide
- 6000 hours average life
- **Horizontal burn position only**
- Color temperature - 4200K
- Replacement Part No. 03.0250

Fiber Capacity:

- 500 fibers - PAF30 fibers
- 288 fibers - Ultra SideGlow™ (PAF40)

Sound:

- 45db rating

Power Consumption:

- 600 Watts, maximum

Safety Features:

- Internal 185°F / 85°C thermal protector

Ambient Operating Temperature:

- -20°F to 110°F
- -29°C to 44°C

Dimensions:

- 12 x 13.88 x 7.13\*\*
- 305mm x 353mm x 181mm\*  
18.6"H (472mm)with door open
- \*add 2.5" (63.5mm) for fiber head
- Allow an additional 5" (127mm) for fiberhead and fiber to "W" position.

Weight:

- 27 lbs.
- 12.2 kg

Material / Finish:

- Galvanneal
- Powder coating, no bare metal inside or outside
- Water, corrosion and chemical resistant

Mounting / Installation:

- Surface or (wall mount - horizontal fiberhead direction only.) Must be flush mounted to surface for proper air separation between compartments.

Ventilation:

- 115 CFM enclosure cooling

Warranty:

- 1 Year (excluding lamp)

## ORDERING INFORMATION

MODEL	POWER	COLOR WHEEL	CONTROL SYSTEM
Eclipse II - 250 watt metal halide	120 - 120 VAC, 60 Hz 220 - 220-240 VAC, 50 Hz 277 - 277 VAC, 50 Hz	N - None 4S-SB - 4 standard 6S-SB - 6 standard 8S-SB - 8 standard 4C-SB - 4 custom 8C-SB - 8 custom <i>Note: Refer to color chart for options.</i>	N - None S - Synchronous D - DMX 512 compatible MS - 300C master module/sync.