



DESCRIPTION

sv150T - Tower illuminator
 150 watt metal halide lamp
 10,000 hour lamp life
 550 strand fiber capacity

SPECIFICATION FEATURES

UL Listed for Wet Locations
 Electrical Rating:
 • 120 VAC, 60 Hz / 3 Amps (start up)
 • 120 VAC, 60 Hz / 1.8 Amps (running)
 • 220-240 VAC, 50 Hz / 3.0 Amps (start up)
 • 220-240 VAC, 60 Hz / 1.2 Amps (running)
 Transformer:
 • Magnetic
 Lamp:
 • 150 watt metal halide
 • 10,000 hours average life
 Fiber Capacity:
 • 550 fibers maximum - PAF30
 • 288 fibers - Ultra SideGlow™ PAF40
 Power Consumption:
 • 200 watts max.
 Storage Temperature
 • -40°F to 140°F
 • -40°C to 60°C
 Ambient Operating Temperature:
 • -20°F to 110°F
 • -29°C to 44°C
 Motors:
 • 4 & 8 color systems: 3RPM motor
 • Controlled units: stepper motor

Dimensions:
 • 8.5 x 9.756 x 20"
 • 216mm x 248mm x 508mm
 Weight:
 • 21 lbs.
 • 9.5 kg.
 Material/Finish:
 • UV stabilized materials
 • Water, corrosion and chemical resistant
 Mounting / Installation:
 • Surface or burial mount
 Standard Features:
 • On/off power and color wheel switch
 Fan:
 • 80,000 life hours
 • 120 VAC, 60Hz, 115 CFM, 20 watts
 Ventilation:
 • Forced ventilation 115 CFM,
 6" clearance required to nearest
 surface. 2' clearance between each
 illuminator.
 Warranty:
 • 1 Year (excluding lamp)

ORDERING INFORMATION

<p>VOLTAGE 150T - 150 watt metal halide</p>	<p>POWER 120 - 120 VAC, 60Hz 220 - 220 VAC, 50 Hz</p>	<p>COLOR WHEEL N - None 4S-SB - 4 standard 8S-SB - 8 standard 4C-SB - 4 custom 8C-SB - 8 custom <i>Note: Refer to color chart for options</i></p>	<p>CONTROL SYSTEM N - None C - Sync./instant color change</p>