



TECHNICAL SPECIFICATIONS SUPERVISION

VER. 1.0


EndGlow®




SV4EG




SV8EG




SV12EG




SV25EG




SV50EG




SV75EG




SV100EG



SV150EGW*



SV225EGW*



SV300EGW*

**White Jacket Only*

PROJECT:	_____
TYPE:	_____
VOLTAGE:	_____
NOTES:	_____

DESCRIPTION

Ideal for use with architectural lighting fixtures, landscape fixtures, water-tight lenses, feature lights, and adaptable for EndGlow® signage.

*Note: When ordering cable, specify length by quantity in terms of feet. Spools are established lengths and will not be cut shorter; if specific lengths are required, order each individual cable cut to length. SV150EG, SV225EG, SV300EG, SV100EG, SV150EGW, SV225EGW, and SV300EGW are not available in 1000' spool lengths.

SPECIFICATION FEATURES

Construction

EndGlow® cable is multistrand fibers protected in a flexible PVC jacket for ease of handling and fiber protection.

Cabling

Diameters are based on fiber quantity:

4 fibers:	.125"	3.2mm	75 fibers:	.375"	9.5mm
8 fibers:	.187"	4.8mm	10 fibers:	.5"	12.5mm
12 fibers:	.219"	5.5mm	150 fibers:	.281"	15.1mm
25 fibers:	.25"	6.35mm	225 fibers:	.625"	15.9mm
50 fibers:	.312"	7.9mm	300 fibers:	.687"	17.5mm

ORDERING INFORMATION

ENDGLOW® CABLES
(Order separately)

SV4EG	4 fibers
SV8EG	8 fibers
SV12EG	12 fibers
SV25EG	25 fibers
SV50EG	50 fibers
SV75EG	75 fibers
SV100EG	100 fibers
SV150EGW	150 fibers
SV225EGW	225 fibers
SV300EGW	300 fibers